

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 813 014 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
17.12.1997 Bulletin 1997/51

(51) Int Cl.⁶: **F16L 33/26, F16L 25/00**

(21) Application number: **97830283.4**

(22) Date of filing: **11.06.1997**

(84) Designated Contracting States:
**AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC
NL PT SE**

(72) Inventor: **Lai, Giovanni, Emiflex S.p.A.
20039 Varedo (Milano) (IT)**

(30) Priority: **11.06.1996 IT MI960429 U**


(74) Representative: **Cicogna, Franco
Ufficio Internazionale Brevetti
Dott.Prof. Franco Cicogna
Via Visconti di Modrone, 14/A
20122 Milano (IT)**

(71) Applicant: **Emiflex S.p.A.
20039 Varedo (Milano) (IT)**

(54) **A flexible and extensible tubular element for coupling gas appliances to a gas delivery system**

(57) The present invention relates to a tubular element construction, which has been specifically designed for coupling gas appliances to a gas delivery system, comprising a bellows-like metal tubular element, coupled to a fitting end piece.

The main feature of the invention is that the tubular element comprises moreover a plastics material protective sheath, arranged on the outside of said metal tubular element and connected to flexible sleeve elements which can be in turn connected to the mentioned fitting end pieces.



BEST AVAILABLE COPY

EP 0 813 014 A2

Description

BACKGROUND OF THE INVENTION

The present invention relates to a flexible and extensible tubular element for coupling gas appliances to a gas delivery system.

As is known, enforcing rules related to gas delivery systems provide to use flexible tubular elements for coupling the gas appliances to the gas delivery system, said flexible tubular elements being made of bellows-like metal tubular sections, substantially made of stainless steel materials, and provided with a bellows construction so as to allow the tubular element length to be increased so as to fit a particular application.

Even if the disclosed construction is rather satisfactory from several standpoints, it, however, has the drawback that it can be damaged, under particular conditions, by atmospheric and outer agents such as, for example, fat materials and the like, which, by adhering to the surface of the tubular element may corrode it with great consequent disadvantages.

SUMMARY OF THE INVENTION

Accordingly, the aim of the present invention is to overcome the above mentioned drawbacks by providing such a flexible and extensible tubular element preventing any possible contact with the outer surface of the metal tubular member, thereby overcoming any possible corrosion phenomena.

Within the scope of the above mentioned aim, a main object of the present invention is to provide such a flexible and extensible tubular element construction allowing to provide an outer sheath for the metal tubular element, thereby providing a further barrier preventing the inner tubular element from being damaged.

Another object of the present invention is to provide such a flexible and extensible tubular element construction which, owing to the specifically designed constructional features thereof, is very reliable and safe in operation.

Yet another object of the present invention is to provide such a flexible and extensible tubular element construction, specifically designed for connecting gas appliances to a gas delivery system, which can be easily made starting from easily commercially available elements and materials and which, moreover, is very competitive from a mere economic standpoint.

According to one aspect of the present invention, the above mentioned aim and objects, as well as yet other objects, which will become more apparent hereinafter, are achieved by a flexible and extensible tubular element construction, specifically designed for coupling gas appliances to a gas delivery system, which comprises a bellows-like metal tubular element, coupled to a fitting end-piece, characterized in that said flexible and extensible tubular element construction comprises more-

over a plastics material protective sheath arranged outside of said metal tubular element and connected to flexible sleeve elements, in turn connectable to said fitting end-piece.

BRIEF DESCRIPTION OF THE DRAWINGS

Further characteristics and advantages of the subject matter of the present invention will become more apparent hereinafter from the following detailed disclosure of a flexible and extensible tubular element construction, specifically designed for coupling gas appliances to a gas delivery system, which is illustrated, by way of an indicative, but not limitative, example in the figures of the accompanying drawings, where:

Figure 1 is a schematic partially broken-away view illustrating the flexible and extensible tubular element according to the present invention;

Figure 2 illustrates, on an enlarged scale, a detail of an end portion of the flexible and extensible tubular element, and clearly showing the fitting end piece therefor, as well as a related flexible sleeve element;

Figure 3 illustrates a plastics material protective sheath element; and

Figure 4 is a cross-sectional view, on an enlarged scale, illustrating a detail of the flexible and extensible sleeve element.

DESCRIPTION OF THE PREFERRED EMBODIMENT

With reference to the number references of the above mentioned figures, the flexible and extensible tubular element construction, specifically designed for coupling gas appliances to a gas delivery system, which construction has been generally indicated by the reference number 1, comprises a bellows-like metal tubular element 2, which is preferably made of stainless steel and has a bellows-like construction, so as to be easily bent and elongated.

At the end portions thereof, the bellows-like metal tubular element is coupled to fitting endpieces, generally indicated by the reference number 5, which are advantageously constituted by a barrel or bush element 6, rigidly associated with the end-portion of the tubular element 2 and engaging with a rotatable nut, generally indicated by the reference number 7.

The main feature of the present invention is that a protective sheath 10 is moreover provided, said protective sheath having a bellows-like shape too and being made of a plastics material, for example that plastics material commercially known with the trade name of "Moplen".

The sheath 10, at the end portions thereof, is coupled to flexible sleeve elements 11 which, at an end thereof, are provided with recesses 12 for engaging the sheath 10 and, at another end thereof, being provided

with a plurality of circumferential ribs 13.

Between the sleeve 11 and the tubular element, an insert 20 can be arranged, said insert being provided with slots 21 engaging with the mentioned ribs 13 so as to firmly lock the sleeve with respect to the fitting end-piece 5.

As shown, the insert 20 is provided with a groove 25, in which a sealing O-ring is engaged, for properly sealing the fitting end-piece.

In the disclosed arrangement, an outer plastics material sheath is provided, which fully covers the flexible tubular metal element, thereby preventing the latter from being damaged by atmospheric agents or other damaging outer agents, thereby overcoming any corrosion problems.

From the above disclosure, it should be apparent that the invention fully achieves the intended aim and objects.

In particular, a protective sheath has been provided, which can be easily applied even on already existing tubular elements.

In practicing the invention, the used materials, provided that they are compatible to the intended use, as well as the contingent size and shapes, can be any, depending on requirements.



gaging therein a sealing O-ring, for sealing said fitting end-piece.

5. A tubular element construction according to one or more of the preceding claims, characterized in that said plastics material protective sheath has a bellows-like construction.
6. A tubular element construction according to one or more of the preceding claims, characterized in that said protective sheath is made of "Moplen".
7. A tubular element construction, characterized in that said tubular element is flexible and extensible.
8. A tubular element construction, specifically designed for coupling gas appliances to a gas delivery system, and substantially as broadly disclosed and illustrated for the intended aim and objects.

Claims

1. A flexible and extensible tubular element construction, specifically designed for coupling gas appliances to a gas delivery system, which comprises a bellows-like metal tubular element, coupled to a fitting end-piece, characterized in that said flexible and extensible tubular element construction comprises moreover a plastics material protective sheath arranged outside of said metal tubular element and connected to flexible sleeve elements, in turn connectable to said fitting end-piece.
2. A tubular element construction according to Claim 1, characterized in that said tubular element construction comprises moreover insert means which can be coupled between said flexible sleeve and fitting end-piece, for clamping said sheath on said bellows-like metal tubular element.
3. A tubular element construction according to Claims 1 and 2, characterized in that said sleeves are provided, at an end portion thereof, with inner recesses for engaging said protective sheath and, at another end portion thereof, with circumferential ribs which can be engaged in corresponding circumferential slots formed on said insert means.
4. A tubular element construction according to one or more of the preceding claims, characterized in that said insert means are provided with a groove for en-

BEST AVAILABLE COPY






FIG. 4




FIG. 3

BEST AVAILABLE COPY

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 813 014 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
05.04.2000 Bulletin 2000/14

(51) Int Cl.7: **F16L 33/26**, F16L 25/00,
F16L 11/15

(43) Date of publication A2:
17.12.1997 Bulletin 1997/51

(21) Application number: **97830283.4**

(22) Date of filing: **11.06.1997**

(84) Designated Contracting States:
**AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC
NL PT SE**

(30) Priority: **11.06.1996 IT MI960429 U**

(71) Applicant: **Emiflex S.p.A.**
20039 Varedo (Milano) (IT)

(72) Inventor: **Lai, Giovanni, Emiflex S.p.A.**
20039 Varedo (Milano) (IT)

(74) Representative: **Cicogna, Franco**
Ufficio Internazionale Brevetti
Dott.Prof. Franco Cicogna
Via Visconti di Modrone, 14/A
20122 Milano (IT)

(54) **A flexible and extensible tubular element for coupling gas appliances to a gas delivery system**

(57) The present invention relates to a tubular element construction (1), which has been specifically designed for coupling gas appliances to a gas delivery system, comprising a bellows-like metal tubular element (2), coupled to a fitting end piece (5).

The main feature of the invention is that the tubular element comprises moreover a plastics material protective sheath (10), arranged on the outside of said metal tubular element and connected to flexible sleeve elements which can be in turn connected to the mentioned fitting end pieces.




FIG. 1

BEST AVAILABLE COPY

EP 0 813 014 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 97 83 0283

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	US 5 423 578 A (KANOMATA SHINICHI ET AL) 13 June 1995 (1995-06-13)	1,2,6,7	F16L33/26 F16L25/00 F16L11/15
Y	* column 4, line 9 - column 4, line 68; figure 2 *	5	
X	US 4 630 850 A (SAKA YOSHIMI) 23 December 1986 (1986-12-23)	1,2,4,6,7	
Y	* column 5, line 67 - column 6, line 22; figures 7,8 *	5	
Y	DE 94 04 268 U (RUFFER EKKEHARD DIPL ING) 5 May 1994 (1994-05-05)	5	
	* page 5, line 16 - page 5, line 22; figure 1 *		
A	GB 2 123 106 A (SMITHS INDUSTRIES PLC) 25 January 1984 (1984-01-25)	1-3,5,6	
X	* page 1, line 83 - page 1, line 97; figure 1 *	7	
A	DE 92 09 073 U (JESCHKE, IMMANUEL) 3 December 1992 (1992-12-03)	1,4	TECHNICAL FIELDS SEARCHED (Int.Cl.6)
X	* page 5, line 21 - page 7, line 12; figure 1 *	7	F16L
The present search report has been drawn up for all claims			
Place of search MUNICH		Date of completion of the search 7 February 2000	Examiner Donnelly, C
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03/82 (P04-C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 97 83 0283

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

07-02-2000

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5423578 A	13-06-1995	JP 6265070 A	20-09-1994
		JP 6265071 A	20-09-1994
		JP 6265072 A	20-09-1994
US 4630850 A	23-12-1986	JP 1647191 C	13-03-1992
		JP 3003837 B	21-01-1991
		JP 60073193 A	25-04-1985
DE 9404268 U	05-05-1994	NONE	
GB 2123106 A	25-01-1984	NONE	
DE 9209073 U	03-12-1992	NONE	

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82